



Slabjack Foundation
2150 Bridge Avenue
Point Pleasant, NJ 08742

(855) 876-5438

Equipment Manager
klomax@slabjack.net

ANCHOR DRIVES - STANDARD RATES

Torque Range	Model Line		Suggested Machine Size	Day	Week	Month
*8,500 ft-lbs	MM10-K	SA-8	Mini Machine/Excavator up to 3.5 Tons	\$ 175	\$ 650	\$ 1,950
*12,500 ft-lbs	SA-12		Excavator between 6 - 12 Tons	\$ 225	\$ 900	\$ 2,700
*26,500 ft-lbs	30K-ADS		Excavator between 8 - 20 Tons	\$ 300	\$ 1,200	\$ 3,600
*69,000 ft-lbs	SD-95 **		Excavator minimum 15 Tons	\$ 675	\$ 2,700	\$ 8,100
			SD Jib Extension	\$ 280	\$ 600	\$ 1,200
*147,000 ft-lbs	MD-190 **		Excavator minimum 25 Tons	\$ 1,200	\$ 4,800	\$ 14,400
			MD Jib Extension	\$ 380	\$ 800	\$ 1,600
*200,000 ft-lbs	UD-300	TA-200	Excavator minimum 45 Tons	\$ 1,350	\$ 5,400	\$ 16,200
			UD Jib Extension	\$ 380	\$ 800	\$ 1,600
*300,000 ft-lbs	RV-300	TA-300	Excavator minimum 50 Tons	\$ 1,900	\$ 7,600	\$ 22,800

* Up To

** High Pressure Anchor Drives Available

CALIBRATED TORQUE MONITORS - STANDARD RATES

Torque	Specs		Description	Day	Week	Month
Up to 70K	Catalog	Quick Start	~ Includes Calibration within one year of project start date. ~ Special calibration services are subject to additional charges.	\$ 225	\$ 850	\$ 2,550
Up to 250K				\$ 475	\$ 1,950	\$ 5,850
Up to 375K				\$ 550	\$ 2,150	\$ 6,450

- ~ Anchor Drives should be sized per the minimum requirements of the engineered designs and specifications.
- ~ Torque specifications depend on the overall efficiencies of the hydraulic system.
- ~ All prices subject to change. Please request a formal quote. Discounts may apply.
- ~ All Equipment is subject to availability.
- ~ Energi Pressure Management Systems by Dinamic Oil are available for compatible units; but are not considered a calibrated torque monitoring device.

Rates Valid through 30.SEPT.2026